FT965-27



FULL THROTTLE SERIES | HIGH CRANKING AGM

CYCLING CAPACITY

20 Hour Rate	**100 Amp Hours**

RESERVE CAPACITY

Reserve @25 AMPS	**142 Minutes**	Reserve @75 AMPS	**40 Minutes**

ELECTRICAL SPECIFICATIONS

Nominal Voltage	**12 Volt**
C100	**110 AH**
C20	**100 AH**
C5	**81 AH**
Short Circuit Current	**5000 Amps**
CCA	**965 Amps**
CA or MCA	**1170 Amps**
PHCA	**1950 Amps**
Internal Resistance	**2.5 mΩ**

MECHANICAL SPECIFICATIONS


Group Size	**27**	
Terminal Type	**DT**	
Terminal Torque	**See reverse side**	
Height (w/ terminal)	**9.33”**	**237 mm**
Height (case only)	**8.43”**	**214 mm**
Width	**6.65”**	**169 mm**
Length	**12.09”**	**307 mm**
Weight	**69.5 lbs**	**31.5 kg**
Case Type	**ABS Plastic -** Flame Res. Rating UL94-HB	

DISCHARGE TABLE (Constant Current)

Time	Amps	Rate
20hr	5.0	0.05 CA
10hr	9.1	0.10 CA
8hr	10.9	0.13 CA
5hr	17.2	0.25 CA
3hr	25.1	0.33 CA
2hr	34.0	0.50 CA
1hr	60.0	1.00 CA


DISCHARGE PROFILE (Constant Current)

12-Volt Battery *Temperature: 77°F (25°C)*




- All listed ratings are @ 100% SoC, T=77°F (25°C), 1.75VPC unless otherwise specified.
- Specifications listed are for estimation purposes only. Battery performance can vary depending on application. Battery design subject to change.

BATTERY & TERMINAL DIMENSIONS (All units shown in mm)




Terminal: DT




fullriverbattery.com

TEMPERATURE vs CAPACITY




STATE of CHARGE (SOC) vs OPEN CIRCUIT VOLTAGE (OCV)




CYCLE LIFE vs DEPTH of DISCHARGE (DOD)

*(Based on BCI Testing @ 2-hr Rate)



SELF DISCHARGE vs TIME/TEMPERATURE



Note: "Boost Charge" required @ 75% SoC, Max 50% Soc

TEMPERATURE RANGE SPECIFICATIONS

Condition	Recommended	Maximum	Recommended	Maximum
Storage	5°F to 122°F	-40°F to 160°F	-15°C to 50°C	-40°C to 71°C
Operation	5°F to 104°F	-40°F to 160°F	-15°C to 40°C	-40°C to 71°C
Charge with TC	5°F to 122°F	-40°F to 160°F	-15°C to 50°C	-40°C to 71°C
Charge w/o TC	32°F to 104°F	5°F to 122°F	0°C to 40°C	-15°C to 50°C

***TC=** Temperature Compensation*

CHARGE VOLTAGES

	Battery Voltages			
Charge Stage	**12V**	**24V**	**36V**	**48V**
Bulk	14.4 - 14.7V	28.8 - 29.4V	43.2 - 44.1V	57.6 - 58.8V
Absorption	14.4 - 14.7V	28.8 - 29.4V	43.2 - 44.1V	57.6 - 58.8V
Float	13.6V	27.2V	40.8V	54.6V

TC Factor: (-2mV°F/cell) or (-4mV°C/cell)

TERMINAL TORQUE SPECS

Terminal Type	ft-lbs	in-lbs	Nm
AP, DT *(AP)*, **M6, M6M** *(Stud)*, **TP07** *(AP)* ,**TP08** *(AP)*	**4.2 - 6.0**	**50-70**	**5.6 - 7.9**
FR45	**6.0 - 7.5**	**70-90**	**7.9 - 10.1**
M8	**7.1 - 8.0**	**85-95**	**9.6 - 10.7**
DT *(Stud)*, **M10M** *(Stud)*	**9.2 - 10.4**	**110-125**	**12.2 - 14**

ISO CERTIFIED

9001:2008 Quality Management System
14001:2004 Environmental Management System
18001:2007 Occupational Health & Safety Management System

TPPL TECHNOLOGY

DELIVERY APPROVED!
LAND, SEA & AIR

Fullriver batteries are sealed lead acid batteries made with Absorbed Glass Mat (AGM) technology. The electrolyte is absorbed into the fiberglass separator material rather than in a free-flowing liquid form. Fullriver batteries are non-spillable electric storage batteries. They are excepted from the requirements of DOT's hazardous materials regulations, since they adhere to the requirements of code 49 CFR Section 173.159(D) - **(CLASSIFIED APPROVED: DOT, CFR, HMR49, IATA, ICAO67, IMDG27)**