




NorthStar automotive batteries excel at providing both high reserve capacity and cranking amps, perfect for performance and start-stop technology applications.

- Pure lead AGM technology delivers exceptional CCA ratings
 - and reserve capacity cycling ability
 - Quick starting every time
 - Cycles over 900 times at 50% depth of discharge
- Faster recharge than conventional batteries


- Proudly made in the USA at our state-of-the-art battery plant
 - OEM fit is ensured - built to exact BCI standards
 - Housed in advanced plastics for durability performance and heat resistance
 - Advanced AGM construction means no water levels to check or terminals to clean
- Approved as non-hazardous cargo for ground sea and air transport DOT 49CFR173.159(d), (i) and (ii)

NSB-AGM35

Nominal Technical Specifications




Technical data

Terminal configuration	SAE
Terminal illustration	
Pulse cranking amps	1260 A
CCA rating at -18°C (0°F)	740 A
CA/MCA rating at 0°C (32°F)	880 A
Reserve capacity	115 min
Capacity - 20 hour rate (1.75 vpc)	60 Ah
Internal resistance	3.8 mΩ @ 25°C (77°F)
Short circuit current	3100 A
Warranty	4 years full
Quantity per layer	25
Quantity per pallet	50

All NorthStar batteries are compliant with Battery Council International standards, UL approved and UN2800 certified. NorthStar is registered to ISO 9001 and ISO 14001.

Technical Drawing



QUALITY ASSURED
ISO 9001



Distributed by:

